EXHIBIT A

REDACTED

EXHIBIT B

HOWREY LLP

1299 Pennsylvania Avenue, NW
Washington, DC 20004-2402
T 202.783.0800
F 202.383.6610
www.howrey.com

November 29, 2005

VIA Hand Delivery

Raja Saliba, Esq.
Sughrue Mion, PLLC
2100 Pennsylvania Avenue, N.W.
Washington, D.C. 20037

Re: *Bridgestone Sports Co. v. Acushnet Co.*,
Civil Action No. 05-132 (JJF) (D. Del.)

Dear Mr. Saliba:

Enclosed please find Acushnet production documents bearing bates numbers AB 0061363 - AB 0080140.

Sincerely,

Geneva J. Eaddy
Case Manager

Enclosures

US005779563A

United States Patent [19]

Yamagishi et al.

[11] Patent Number: 5,779,563

[45] Date of Patent: Jul. 14, 1998

[54] MULTI-PIECE SOLID GOLF BALL

[75] Inventors: Hisashi Yamagishi; Yasushi Ichikawa; Atsushi Nakamura, all of Chichibu, Japan

[73] Assignee: Bridgestone Sports Co., Ltd., Tokyo, Japan

[21] Appl. No.: 796,454

[22] Filed: Feb. 10, 1997

Related U.S. Application Data

[60] Provisional application No. 60/017,271 May 13, 1996.

[30] Foreign Application Priority Data

Feb. 9, 1996 [JP] Japan 8-048137

[51] Int. Cl.[6] A63B 37/06; A63B 37/12

[52] U.S. Cl. 473/371; 473/373; 473/384

[58] Field of Search 473/374, 373, 473/384, 372, 377, 378

[56] References Cited

U.S. PATENT DOCUMENTS

4,714,253	12/1987	Nakahara et al.	473/374 X
5,002,281	3/1991	Nakahara et al.	473/374 X
5,497,996	3/1996	Cadorniga	473/378 X
5,553,852	9/1996	Higuchi et al.	473/378 X
5,601,503	2/1997	Yamagishi et al.	473/384

Primary Examiner—George J. Marlo

Attorney, Agent, or Firm—Sughrue, Mion, Zinn, Macpeak & Seas, PLLC

[57] ABSTRACT

A multi-piece solid golf ball comprises a solid core and a cover of at least two layers enclosing the core and having a number of dimples in cover outer layer surface. The solid core is formed of a rubber base and has a specific gravity of at least 1.00. The cover is formed of a thermoplastic resin and the cover outer layer has a greater specific gravity than the core or a cover inner layer. The golf ball has an inertia moment (M) within the range given by the following expression: $M_{DL} \leqq M \leqq M_{UL}$ wherein M_{UL}=0.08D+84.8 and M_{DL}=0.08D+77.8 wherein D is a Shore D hardness of the cover, the dimples occupy at least 60% of the ball surface, and V_0 is in the range of 0.4 to 0.65. The ball is improved in flight distance, controllability, roll and straight travel upon putting.

5 Claims, 2 Drawing Sheets



US005779563A

United States Patent [19]

Yamagishi et al.

[11] Patent Number: 5,779,563

[45] Date of Patent: Jul. 14, 1998

[54] MULTI-PIECE SOLID GOLF BALL

[75] Inventors: Hisashi Yamagishi; Yasushi Ichikawa; Atsushi Nakamura, all of Chichibu, Japan

[73] Assignee: Bridgestone Sports Co., Ltd., Tokyo, Japan

[21] Appl. No.: 796,454

[22] Filed: Feb. 10, 1997

Related U.S. Application Data

[60] Provisional application No. 60/017,271 May 13, 1996.

[30] Foreign Application Priority Data

Feb. 9, 1996 [JP] Japan 8-048137

[51] Int. Cl.[6] A63B 37/06; A63B 37/12

[52] U.S. Cl. 473/371; 473/373; 473/384

[58] Field of Search 473/374, 373, 473/384, 372, 377, 378

[56] References Cited

U.S. PATENT DOCUMENTS

4,714,253	12/1987	Nakahara et al.	473/374 X
5,002,281	3/1991	Nakahara et al.	473/374 X
5,497,996	3/1996	Calcaterra	473/378 X
5,553,852	9/1996	Higuchi et al.	473/378 X
5,601,503	2/1997	Yamagishi et al.	473/384

Primary Examiner—George J. Marlo

Attorney, Agent, or Firm—Sughrue, Mion, Zinn, Macpeak & Seas, PLLC

[57] ABSTRACT

A multi-piece solid golf ball comprises a solid core and a cover of at least two layers enclosing the core and having a number of dimples in cover outer layer surface. The solid core is formed of a rubber base and has a specific gravity of at least 1.00. The cover is formed of a thermoplastic resin and the cover outer layer has a greater specific gravity than the core or a cover inner layer. The golf ball has an inertia moment (M) within the range given by the following expression: $M_{OL} \leq M \leq M_{OL}$ wherein M_{OL}=0.08D+84.8 and M_{OL}= 0.08D+77.8 wherein D is a Shore D hardness of the cover, the dimples occupy at least 60% of the ball surface, and V_0 is in the range of 0.4 to 0.65. The ball is improved in flight distance, controllability, roll and straight travel upon putting.

5 Claims, 2 Drawing Sheets



US005779563A

United States Patent [19]

Yamagishi et al.

[11] Patent Number: 5,779,563

[45] Date of Patent: Jul. 14, 1998

[54] MULTI-PIECE SOLID GOLF BALL

[75] Inventors: Hisashi Yamagishi; Yasushi Ichikawa; Atsushi Nakamura, all of Chichibu, Japan

[73] Assignee: Bridgestone Sports Co., Ltd., Tokyo, Japan

[21] Appl. No.: 794,454

[22] Filed: Feb. 10, 1997

Related U.S. Application Data

[60] Provisional application No. 60/017,271 May 13, 1996.

[30] Foreign Application Priority Data

Feb. 9, 1996 [JP] Japan 8-048137

[51] Int. Cl.[6] A63B 37/06; A63B 37/12

[52] U.S. Cl. 473/371; 473/373; 473/384

[58] Field of Search 473/374, 373, 473/384, 372, 377, 378

[56] References Cited

U.S. PATENT DOCUMENTS

4,714,253 12/1987 Nakahara et al. ..... 473/374 X

5,002,281 3/1991 Nakahara et al. ..... 473/374 X

5,497,996 3/1996 Cadorniga ..... 473/378 X

5,553,852 9/1996 Higuchi et al. ..... 473/378 X

5,601,503 2/1997 Yamagishi et al. 473/384

Primary Examiner—George J. Marlo

Attorney, Agent, or Firm—Sughrue, Mion, Zinn, Macpeak & Seas, PLLC

[57] ABSTRACT

A multi-piece solid golf ball comprises a solid core and a cover of at least two layers enclosing the core and having a number of dimples in cover outer layer surface. The solid core is formed of a rubber base and has a specific gravity of at least 1.00. The cover is formed of a thermoplastic resin and the cover outer layer has a greater specific gravity than the core or a cover inner layer. The golf ball has an inertia moment (M) within the range given by the following expression: $M_{OL} \leq M \leq M_{UL}$ wherein M_{UL}=0.08D+84.8 and M_{OL}=0.08D+77.8 wherein D is a Shore D hardness of the cover, the dimples occupy at least 60% of the ball surface, and V_0 is in the range of 0.4 to 0.65. The ball is improved in flight distance, controllability, roll and straight travel upon putting.

5 Claims, 2 Drawing Sheets



US005779563A

United States Patent [19]

Yamagishi et al.

[11] Patent Number: 5,779,563

[45] Date of Patent: Jul. 14, 1998

[54] MULTI-PIECE SOLID GOLF BALL

[75] Inventors: Hisashi Yamagishi; Yasushi Ichikawa; Atsushi Nakamura, all of Chichibu, Japan

[73] Assignee: Bridgestone Sports Co., Ltd., Tokyo, Japan

[21] Appl. No.: 796,454

[22] Filed: Feb. 10, 1997

Related U.S. Application Data

[60] Provisional application No. 60/017,271 May 13, 1996.

[30] Foreign Application Priority Data

Feb. 9, 1996 [JP] Japan 8-048137

[51] Int. Cl.[6] A63B 37/06; A63B 37/12

[52] U.S. Cl. 473/371; 473/373; 473/384

[58] Field of Search 473/374, 373, 473/384, 372, 377, 378

[56] References Cited

U.S. PATENT DOCUMENTS

4,714,253	12/1987	Nakahara et al.	473/374 X
5,002,281	3/1991	Nakahara et al.	473/374 X
5,397,996	3/1996	Cadorniga	473/378 X
5,553,852	9/1996	Higuchi et al.	473/378 X
5,601,503	2/1997	Yamagishi et al.	473/384

Primary Examiner—George J. Marlo

Attorney, Agent, or Firm—Sughrue, Mion, Zinn, Macpeak & Seas, PLLC

[57] ABSTRACT

A multi-piece solid golf ball comprises a solid core and a cover of at least two layers enclosing the core and having a number of dimples in cover outer layer surface. The solid core is formed of a rubber base and has a specific gravity of at least 1.00. The cover is formed of a thermoplastic resin and the cover outer layer has a greater specific gravity than the core or a cover inner layer. The golf ball has an inertia moment (M) within the range given by the following expression: $M_{OL} \leq M \leq M_{UL}$ wherein M_{UL}=0.08D+84.8 and M_{OL}=0.08D+77.8 wherein D is a Shore D hardness of the cover, the dimples occupy at least 60% of the ball surface, and V_0 is in the range of 0.4 to 0.65. The ball is improved in flight distance, controllability, roll and straight travel upon putting.

5 Claims, 2 Drawing Sheets



US005779563A

United States Patent [19]

Yamagishi et al.

[11] Patent Number: 5,779,563

[45] Date of Patent: Jul. 14, 1998

[54] MULTI-PIECE SOLID GOLF BALL

[75] Inventors: Hisashi Yamagishi; Yasushi Ichikawa; Atsushi Nakamura, all of Chichibu, Japan

[73] Assignee: Bridgestone Sports Co., Ltd., Tokyo, Japan

[21] Appl. No.: 796,454

[22] Filed: Feb. 10, 1997

Related U.S. Application Data

[60] Provisional application No. 60/017,271 May 13, 1996.

[30] Foreign Application Priority Data

Feb. 9, 1996 [JP] Japan 8-048137

[51] Int. Cl.[6] A63B 37/06; A63B 37/12

[52] U.S. Cl. 473/371; 473/373; 473/384

[58] Field of Search 473/374, 373, 473/384, 372, 377, 378

[56] References Cited

U.S. PATENT DOCUMENTS

4,714,253	12/1987	Nakahara et al.	473/374 X
5,002,281	3/1991	Nakahara et al.	473/374 X
5,497,996	3/1996	Cadorniga	473/378 X
5,553,852	9/1996	Higuchi et al.	473/378 X
5,601,503	2/1997	Yamagishi et al.	473/384

Primary Examiner—George J. Marlo

Attorney, Agent, or Firm—Sughrue, Mion, Zinn, Macpeak & Seas, PLLC

[57] ABSTRACT

A multi-piece solid golf ball comprises a solid core and a cover of at least two layers enclosing the core and having a number of dimples in cover outer layer surface. The solid core is formed of a rubber base and has a specific gravity of at least 1.00. The cover is formed of a thermoplastic resin and the cover outer layer has a greater specific gravity than the core or a cover inner layer. The golf ball has an inertia moment (M) within the range given by the following expression: $M_{DL} \leq M \leq M_{UL}$ wherein M_{UL}=0.08D+64.8 and M_{DL}=0.08D+77.8 wherein D is a Shore D hardness of the cover, the dimples occupy at least 60% of the ball surface, and V_0 is in the range of 0.4 to 0.65. The ball is improved in flight distance, controllability, roll and straight travel upon putting.

5 Claims, 2 Drawing Sheets



EXHIBIT C

REDACTED

EXHIBIT D

REDACTED